

# Formatting Syntax

 [DokuWiki](#) supports some simple markup language, which tries to make the datafiles to be as readable as possible. This page contains all possible syntax you may use when editing the pages. Simply have a look at the source of this page by pressing “Edit this page”. If you want to try something, just use the [playground](#) page. The simpler markup is easily accessible via  [quickbuttons](#), too.

## Basic Text Formatting

DokuWiki supports **bold**, *italic*, underlined and monospaced texts. Of course you can ***combine*** all these.

```
DokuWiki supports bold, //italic//, __underlined__ and 'monospaced'
texts.
Of course you can __//'combine'//__ all these.
```

You can use <sub>subscript</sub> and <sup>superscript</sup>, too.

```
You can use <sub>subscript</sub> and <sup>superscript</sup>, too.
```

You can mark something as deleted as well.

```
You can mark something as <del>deleted</del> as well.
```

**Paragraphs** are created from blank lines. If you want to **force a newline** without a paragraph, you can use two backslashes followed by a whitespace or the end of line.

This is some text with some linebreaks

Note that the two backslashes are only recognized at the end of a line  
or followed by  
a whitespace \\this happens without it.

```
This is some text with some linebreaks\\ Note that the
two backslashes are only recognized at the end of a line\\
or followed by\\ a whitespace \\this happens without it.
```

You should use forced newlines only if really needed.

## Links

DokuWiki supports multiple ways of creating links.

## External

External links are recognized automagically: <http://www.google.com> or simply [www.google.com](http://www.google.com) - You can set the link text as well: [This Link points to google](#). Email addresses like this one: [andi@splitbrain.org](mailto:andi@splitbrain.org) are recognized, too.

```
DokuWiki supports multiple ways of creating links. External links are
recognized
automagically: http://www.google.com or simply www.google.com - You can set
link text as well: [[http://www.google.com|This Link points to google]].
Email
addresses like this one: <andi@splitbrain.org> are recognized, too.
```

## Internal

Internal links are created by using square brackets. You can either just give a [pagename](#) or use an additional [link text](#).

```
Internal links are created by using square brackets. You can either just
give
a [[pagename]] or use an additional [[pagename|link text]].
```

 [Wiki pagenames](#) are converted to lowercase automatically, special characters are not allowed.

You can use [namespaces](#) by using a colon in the pagename.

```
You can use [[some:namespaces]] by using a colon in the pagename.
```

For details about namespaces see  [namespaces](#).

Linking to a specific section is possible, too. Just add the section name behind a hash character as known from HTML. This links to [this Section](#).

```
This links to [[syntax#internal|this Section]].
```

Notes:

- Links to [existing pages](#) are shown in a different style from [nonexisting](#) ones.
- DokuWiki does not use  [CamelCase](#) to automatically create links by default, but this behavior can be enabled in the  [config](#) file. Hint: If DokuWiki is a link, then it's enabled.
- When a section's heading is changed, its bookmark changes, too. So don't rely on section linking too much.

## Interwiki

DokuWiki supports  [Interwiki](#) links. These are quick links to other Wikis. For example this is a link to Wikipedia's page about Wikis:  [Wiki](#).

DokuWiki supports `[[doku>Interwiki]]` links. These are quick links to other Wikis.

For example this is a link to Wikipedia's page about Wikis: `[[wp>Wiki]]`.

## Windows Shares

Windows shares like [this](#) are recognized, too. Please note that these only make sense in a homogeneous user group like a corporate [Intranet](#).

Windows Shares like `[[\\server\share|this]]` are recognized, too.

Notes:

- For security reasons direct browsing of windows shares only works in Microsoft Internet Explorer per default (and only in the “local zone”).
- For Mozilla and Firefox it can be enabled through different workaround mentioned in the [Mozilla Knowledge Base](#). However, there will still be a JavaScript warning about trying to open a Windows Share. To remove this warning (for all users), put the following line in `conf/lang/en/lang.php` (more details at [localization](#)): `<code - conf/lang/en/lang.php><?php / * Customization of the english language file * Copy only the strings that needs to be modified */ $lang['js']['nosmblinks'] = ; </code> ===== Image Links ===== You can also use an image to link to another internal or external page by combining the syntax for links and images (see below) like this:`

# LIAM'S CAMPAIGNS



# LIAM'S CAMPAIGNS



Please note: The image formatting is the only formatting syntax accepted in link names. The whole [image](#) and [link](#) syntax is supported (including image resizing, internal and external images and URLs and interwiki links). ===== Footnotes ===== You can add footnotes <sup>1)</sup> by using double parentheses. You can add footnotes <sup>2)</sup> by using double parentheses. ===== Sectioning ===== You can use up to five different levels of headlines to structure your content. If you have more than three headlines, a table of contents is generated automatically – this can be disabled by including the string `~~NOTOC~~` in the document. ===== **Headline Level 3** ===== **Headline Level 4** ===== **Headline Level 5** ===== **Headline Level 3** ===== **Headline Level 4** ===== **Headline Level 5** ===== By using four or more dashes, you can make a horizontal line: `--` ===== **Media Files** ===== You can include external and internal [images](#), [videos](#) and [audio files](#) with curly brackets. Optionally you can specify the size of them. Real size:

# LIAM'S CAMPAIGNS



Resize to given width:



Resize to given width and height<sup>3)</sup>:

Resized external image:



Real size:

# LIAM'S CAMPAIGNS



Resize to given width:



Resize to given width and height:



Resized external image:




choose the alignment.

By using left or right whitespaces you can

# LIAM'S CAMPAIGNS



# LIAM'S CAMPAIGNS



# LIAM'S CAMPAIGNS



# LIAM'S CAMPAIGNS



# LIAM'S CAMPAIGNS





Of course, you can add a title (displayed as a tooltip by most browsers), too.

# LIAM'S CAMPAIGNS



# LIAM'S CAMPAIGNS



For linking an image to another page see [Image Links](#) above. ===== Supported Media Formats ===== DokuWiki can embed the following media formats directly. | Image | gif, jpg, png | | Video | webm, ogv, mp4 | | Audio | ogg, mp3, wav | | Flash | swf | If you specify a filename that is not a supported media format, then it will be displayed as a link instead. By adding ?linkonly you provide a link to the media without displaying it inline [dokuwiki-128.png](#) [dokuwiki-128.png](#) This is just a link to the image. ===== Fallback Formats ===== Unfortunately not all browsers understand all video and audio formats. To mitigate the problem, you can upload your file in different formats for maximum browser compatibility. For example consider this embedded mp4 video: When you upload a video.webm and video.ogv next to the referenced video.mp4, DokuWiki will automatically add them as alternatives so that one of the three files is understood by your browser. Additionally DokuWiki supports a "poster" image which will be shown before the video has started. That image needs to have the same filename as the video and be either a jpg or png file. In the example above a video.jpg file would work. ===== Lists ===== Dokuwiki supports ordered and unordered lists. To create a list item, indent your text by

two spaces and use a \* for unordered lists or a - for ordered ones. \* This is a list \* The second item \* You may have different levels \* Another item - The same list but ordered - Another item - Just use indentation for deeper levels - That's it <code> \* This is a list \* The second item \* You may have different levels \* Another item - The same list but ordered - Another item - Just use indentation for deeper levels - That's it </code> Also take a look at the [FAQ on list items](#). =====

Text Conversions ===== DokuWiki can convert certain pre-defined characters or strings into images or other text or HTML. The text to image conversion is mainly done for smileys. And the text to HTML conversion is used for typography replacements, but can be configured to use other HTML as well. ===== Text to Image Conversions ===== DokuWiki converts commonly used [emoticons](#) to their graphical equivalents. Those [Smileys](#) and other images can be configured and extended. Here is an

overview of Smileys included in DokuWiki: \*  8-) \*  8-0 \*   
 :- ( \*  :- ) \*  =) \*  :- / \*  :- \ \*  :- ? \*  :- D \*  
 :- P \*  :- 0 \*  :- X \*  :- | \*  ; - ) \*  ^ ^ \*   
 m( \*  :?: \*  !: : \*  LOL \*  **Fix Me!** FIXME \*

 **Delete!**

DELETEME ===== Text to HTML Conversions =====

Typography: [DokuWiki](#) can convert simple text characters to their typographically correct entities. Here is an example of recognized characters. → ← ↔ ⇒ ⇐ ⇔ » « – — 640×480 © ™ ® “He thought 'It's a man's world'...” <code> → ← ↔ ⇒ ⇐ ⇔ » « – — 640×480 © ™ ® “He thought 'It's a man's world'...” </code> The same can be done to produce any kind of HTML, it just needs to be added to the [pattern file](#). There are three exceptions which do not come from that pattern file: multiplication entity (640×480), 'single' and “double quotes”. They can be turned off through a [config option](#). =====

Quoting ===== Some times you want to mark some text to show it's a reply or comment. You can use the following syntax: <code> I think we should do it > No we shouldn't » Well, I say we should > Really? » Yes! »> Then lets do it! </code> I think we should do it > No we shouldn't » Well, I say we should > Really? » Yes! »> Then lets do it! =====

Tables ===== DokuWiki supports a simple syntax to create tables. ^ Heading 1 ^ Heading 2 ^ Heading 3 ^ | Row 1 Col 1 | Row 1 Col 2 | Row 1 Col 3 | | Row 2 Col 1 | some colspan (note the double pipe) || | Row 3 Col 1 | Row 3 Col 2 | Row 3 Col 3 | Table rows have to start and end with a | for normal rows or a ^ for headers. ^ Heading 1 ^ Heading 2 ^ Heading 3 ^ | Row 1 Col 1 | Row 1 Col 2 | Row 1 Col 3 | | Row 2 Col 1 | some colspan (note the double pipe) || | Row 3 Col 1 | Row 3 Col 2 | Row 3 Col 3 | To connect cells horizontally, just make the next cell completely empty as shown above. Be sure to have always the same amount of cell separators! Vertical tableheaders are possible, too. | ^ Heading 1 ^ Heading 2 ^ ^ Heading 3 | Row 1 Col 2 | Row 1 Col 3 | ^ Heading 4 | no colspan this time | | ^ Heading 5 | Row 2 Col 2 | Row 2 Col 3 | As you can see, it's the cell separator before a cell which decides about the formatting: | ^ Heading

```

1 ^ Heading 2 ^ ^ Heading 3 | Row 1 Col 2 | Row 1 Col 3 | ^ Heading 4 |
no colspan this time | | ^ Heading 5 | Row 2 Col 2 | Row 2 Col 3 | You
can have rowspans (vertically connected cells) by adding ::: into the
cells below the one to which they should connect. ^ Heading 1 ^ Heading
2 ^ Heading 3 ^ | Row 1 Col 1 | this cell spans vertically | Row 1 Col 3
| | Row 2 Col 1 | ::: | Row 2 Col 3 | | Row 3 Col 1 | ::: | Row 2 Col 3
| Apart from the rowspan syntax those cells should not contain anything
else. ^ Heading 1 ^ Heading 2 ^ Heading 3 ^ | Row 1 Col 1 | this cell
spans vertically | Row 1 Col 3 | | Row 2 Col 1 | ::: | Row 2 Col 3 | |
Row 3 Col 1 | ::: | Row 2 Col 3 | You can align the table contents, too.
Just add at least two whitespaces at the opposite end of your text: Add
two spaces on the left to align right, two spaces on the right to align
left and two spaces at least at both ends for centered text. ^ Table
with alignment ^^^ | right| center |left | |left | right| center | |
xxxxxxxxxxxxx | xxxxxxxxxxxxxx | xxxxxxxxxxxxxx | This is how it looks in the
source: ^ Table with alignment ^^^ | right| center |left | |left |
right| center | | xxxxxxxxxxxxxx | xxxxxxxxxxxxxx | xxxxxxxxxxxxxx | Note:
Vertical alignment is not supported. ===== No Formatting ===== If you
need to display text exactly like it is typed (without any formatting),
enclose the area either with <nowiki> tags or even simpler, with double
percent signs %%. This is some text which contains addresses like this:
http://www.splitbrain.org and **formatting**, but nothing is done with
it. The same is true for //__this__ text// with a smiley ;-). This is
some text which contains addresses like this: http://www.splitbrain.org
and **formatting**, but nothing is done with it. The same is true for
//__this__ text// with a smiley ;-). ===== Code Blocks ===== You can
include code blocks into your documents by either indenting them by at
least two spaces (like used for the previous examples) or by using the
tags <code> or <file>. This is text is indented by two spaces. <code>
This is preformatted code all spaces are preserved: like <-this </code>
<file> This is pretty much the same, but you could use it to show that
you quoted a file. </file> Those blocks were created by this source:
This is text is indented by two spaces. <code> This is preformatted code
all spaces are preserved: like <-this </code> <file> This is pretty much
the same, but you could use it to show that you quoted a file. </file>
===== Syntax Highlighting ===== DokuWiki can highlight sourcecode, which
makes it easier to read. It uses the GeSHi Generic Syntax Highlighter –
so any language supported by GeSHi is supported. The syntax uses the
same code and file blocks described in the previous section, but this
time the name of the language syntax to be highlighted is included
inside the tag, e.g. <codejava> or <filejava>. <code java> / * The
HelloWorldApp class implements an application that * simply displays
“Hello World!” to the standard output. */ class HelloWorldApp { public
static void main(String[] args) { System.out.println(“Hello World!”);
Display the string. } } </code> The following language strings are
currently recognized: 4cs 6502acme 6502kickass 6502tasm 68000devpac abap
actionsript3 actionsript ada aimms algol68 apache applescript
aptsources arm asm asp asymptote autoconf autohotkey autoit avisynth awk
bascomavr bash basic4gl batch bf biblatex bibtex blitzbasic bnf boo
caddcl cadlisp ceylon cfdg cfm chaiscript chapel cil cloadrunner clojure
cmac cmake cobol coffeescript c cpp cpp-qt cpp-winapi csharp css

```

cuesheet cwinapi dart dcl dcpu16 dcs delphi diff div dos dot d  
 ecmascript eiffel email epc e erlang euphoria ezt f1 falcon fo fortran  
 freebasic freeswitch fsharp gambas gdb genero genie gettext glsl gml  
 gnuplot go groovy gwbasic haskell haxe higest hq9plus html html4strict  
 html5 icon idl ini inno intercal io isppanel java5 java javascript jcl  
 j jquery julia kixtart klonec klonecpp kotlin latex lb ldif lisp llvm  
 locobasic logtalk lolcode lotusformulas lotusscript lscript lsl2 lua  
 m68k magiksf make mapbasic mathematica matlab mercury metapost mirc  
 mk-61 mmix modula2 modula3 mpasm mxml mysql nagios netrexx newlisp nginx  
 nimrod nsis oberon2 objc object ocaml-brief ocaml octave oobas oorexx  
 oracle11 oracle8 oxygene oz parasail parigp pascal pcre perl6 perl per  
 pf phix php-brief php pic16 pike pixelbender pli plsqli postgresql  
 postscript povray powerbuilder powershell proftpd progress prolog  
 properties providex purebasic pycon pys60 python qbasic qml q racket  
 rails rbs rebol reg rexx robots roff rpmspec rsplus ruby rust sas sass  
 scala scheme scilab scl sdlbasic smalltalk smarty spark sparql sql  
 sshconfig standardml stonesscript swift systemverilog tclegg tcl teraterm  
 texgraph text thinbasic tsql twig typoscript unicon upc urbi uscript  
 vala vbnet vb vbscript vedit verilog vhdl vim visualfoxpro visualprolog  
 whitespace whois winbatch wolfram xbasic xml xoyo xorg\_conf xpp yaml z80  
 zbasic

*There are additional [advanced options](#) available for syntax highlighting, such as highlighting lines or adding line numbers. ===== Downloadable Code Blocks ===== When you use the <code> or <file> syntax as above, you might want to make the shown code available for download as well. You can do this by specifying a file name after language code like this: <code> <file php myexample.php> <?php echo "hello world!"; ?> </file> </code> <file php myexample.php> <?php echo "hello world!"; ?> </file> If you don't want any highlighting but want a downloadable file, specify a dash (-) as the language code: <code - myfile.foo>. =====*

**RSS/ATOM Feed Aggregation =====** [DokuWiki](#) can integrate data from external XML feeds. For parsing the XML feeds, [SimplePie](#) is used. All formats understood by SimplePie can be used in DokuWiki as well. You can influence the rendering by multiple additional space separated parameters: ^ Parameter ^ Description ^ | any number | will be used as maximum number items to show, defaults to 8 | | reverse | display the last items in the feed first | | author | show item authors names | | date | show item dates | | description | show the item description. All HTML tags will be stripped | | nosort | do not sort the items in the feed | | n[dhm] | refresh period, where d=days, h=hours, m=minutes. (e.g. 12h = 12 hours). | The refresh period defaults to 4 hours. Any value below 10 minutes will be treated as 10 minutes. [DokuWiki](#) will generally try to supply a cached version of a page, obviously this is inappropriate when the page contains dynamic external content. The parameter tells [DokuWiki](#) to re-render the page if it is more than refresh period since the page was last rendered. By default the feed will be sorted by date, newest items first. You can sort it by oldest first using the reverse parameter, or display the feed as is with nosort. **Example:**

- [EA Lays Off Staff Across All Battlefield Studios Following Record-Breaking Battlefield 6 Launch](#) by BeauHD (2026/03/09 23:00)
- [Live Nation Avoids Ticketmaster Breakup By 'Open Sourcing' Their Ticketing Model](#) by

BeauHD (2026/03/09 22:00)

- [How AI Assistants Are Moving the Security Goalposts](#) by BeauHD (2026/03/09 21:00)
- [Bluesky CEO Jay Graber Is Stepping Down](#) by BeauHD (2026/03/09 20:00)
- [Qualcomm's New Arduino Ventuno Q Is an AI-Focused Computer Designed For Robotics](#) by BeauHD (2026/03/09 19:00)
- [EA Lays Off Staff Across All Battlefield Studios Following Record-Breaking Battlefield 6 Launch](#) by BeauHD (2026/03/09 23:00)
- [Live Nation Avoids Ticketmaster Breakup By 'Open Sourcing' Their Ticketing Model](#) by BeauHD (2026/03/09 22:00)
- [How AI Assistants Are Moving the Security Goalposts](#) by BeauHD (2026/03/09 21:00)
- [Bluesky CEO Jay Graber Is Stepping Down](#) by BeauHD (2026/03/09 20:00)
- [Qualcomm's New Arduino Ventuno Q Is an AI-Focused Computer Designed For Robotics](#) by BeauHD (2026/03/09 19:00)

==== Control Macros ==== Some syntax influences how DokuWiki renders a page without creating any output it self. The following control macros are available: ^ Macro ^ Description | |  
 ~~NOTOC~~ | If this macro is found on the page, no table of contents will be created | |  
 ~~NOCACHE~~ | DokuWiki caches all output by default. Sometimes this might not be wanted (eg. when the <php> syntax above is used), adding this macro will force DokuWiki to rerender a page on every call |  
 ==== Syntax Plugins ==== DokuWiki's syntax can be extended by  [Plugins](#). How the installed plugins are used is described on their appropriate description pages. The following syntax plugins are available in this particular DokuWiki installation:

- [Add New Page plugin 2025-09-21](#) by [Damien Regad](#), [Benjamin Santalucia](#), [Sam Wilson](#) and other contributors  
Adds a "new page form" to any wiki page.
- [Ad-Hoc Tables Plugin 2023-04-20](#) by [Sascha Leib](#)  
Enables HTML markup Tables (under development!)
- [Ad-Hoc HTML Plugin 2025-05-14](#) by [Sascha Leib](#)  
(Formerly: Ad Hoc Tags) A secure but flexible way to insert HTML tags into DokuWiki
- [Bookcreator Plugin 2024-02-07](#) by [Gerrit Uitslag](#) (previous: [Luigi Micco](#))  
Allow to make a book (PDF, ODT, HTML or text) from selected pages
- [Bootstrap Wrapper Plugin 2022-09-22](#) by [Giuseppe Di Terlizzi](#)  
Bootstrap Wrapper for DokuWiki
- [Bureaucracy Plugin 2025-03-06](#) by [Andreas Gohr](#)  
Create forms and generate pages or emails from them
- [Structured Data Plugin 2024-01-30](#) by [Andreas Gohr](#)  
Add and query structured data in your wiki
- [Diagram plugin 2021-02-21](#) by [Nikita Melnichenko](#)  
Constructs diagrams
- [Dw2Pdf plugin 2023-11-25](#) by [Andreas Gohr](#) and [Luigi Micco](#)  
DokuWiki to PDF converter
- [Gallery Plugin 2024-04-30](#) by [Andreas Gohr](#)  
Creates a gallery of images from a namespace or RSS/ATOM feed
- [hidepages plugin 2013-08-02](#) by [Matthias Schulte](#)  
Hide pages from search results and/or sitemap
- [iframe plugin 2023-08-17](#) by [Christopher Smith](#)  
Allows external URLs to be loaded into an iframe in your DokuWiki page.
- [imapmarkers plugin 2023-05-25](#) by [Kai Thoene](#)  
Image Maps With Markers
- [include plugin 2025-07-22](#) by [Michael Hamann](#), [Gina Häussge](#), [Christopher Smith](#), [Michael](#)

[Klier, Esther Brunner](#)

Functions to include another page in a wiki page

- [Indexmenu Plugin 2024-01-05](#) by [Samuele Tognini](#), [Gerrit Uitslag](#)  
Show a customizable and sortable index for a namespace
- [Info Plugin 2020-06-04](#) by [Andreas Gohr](#)  
Displays information about various DokuWiki internals
- [Markdowku 2021-12-04](#) by [Julian Fagir](#), [Raphael Wimmer \(maintainer\)](#)  
Integrates Markdown into Dokuwiki syntax
- [nodisp 2022-09-14](#) by [Myron Turner](#)  
Hide text from browser display or remove from output to browser depending on acl
- [Open Document Plugin 2023-03-03](#) by [Andreas Gohr](#), [Aurelien Bompard](#), [Florian Lamml](#), [LarsDW223](#)  
Export the current Wiki page to a OpenOffice ODT file
- [Pagelist Plugin 2023-08-27](#) by [Matthias Schulte](#), [Michael Hamann](#), [Michael Klier](#), [Gina Haeussge](#)  
Lists pages in a nice formatted way
- [Tag Plugin 2023-10-17](#) by [Michael Hamann](#), [Gina Häussge](#), [Christopher Smith](#), [Michael Klier](#), [Esther Brunner](#)  
tag wiki pages
- [Wrap Plugin 2023-08-13](#) by [Anika Henke](#)  
Universal plugin which combines functionalities of many other plugins. Wrap wiki text inside containers (divs or spans) and give them a class (choose from a variety of preset classes), a width and/or a language with its associated text direction.

1) 2)

This is a footnote

3)

when the aspect ratio of the given width and height doesn't match that of the image, it will be cropped to the new ratio before resizing

From: <http://wiki.liamgore.co.uk/> - **Liam's Campaigns**

Permanent link: <http://wiki.liamgore.co.uk/doku.php?id=wiki:syntax>

Last update: **2025/12/29 20:41**

